

## Lazure Glaze

### Description

A water-based, non-toxic, fast-drying medium for creating paint effects. Beautifully scented, The Natural Paint Company Lazure Glaze can be used in various ways by layering translucent coats of colour. The paint-effect surface can be sealed with a pure or slightly diluted coat of clear glaze to increase washability and grease and water resistance.

### Uses

To create paint effects, such as rag rolling, stippling, veil painting, marbling, stencilling by mixing a clear glaze with pigments for coating surfaces pre-painted with The Natural Paint Company Wall Paint

- Gib board, wallpaper, plastered walls and timber panelling
- Can also be used as an artist's medium

### Colours

Powder Pigments - available in 50g	
1301	Ebony Black
1302	Red Iron Oxide
1303	Umber
1304	Ochre Red
1305	Ochre Rust Brown
1306	Yellow Orange
1307	Ochre Yellow
1309	Red
1310	Ultramarine Blue
1311	Sun Yellow
1312	Ultramarine Violet
1313	Ultramarine Red
1314	Violet
1315	Spinell Green
1316	Spinell Turquoise
1317	Spinell Blue



## **Coverage**

- 15-20m<sup>2</sup> per litre, depending on absorbency of the substrate, for the dilution recommended in 'Applying the Product – Tinting and Mixing Instructions'.

## **Container Sizes**

- 1 Litre, 2 Litre, 5 Litre for Glaze (see 'Colours' for pigment sizes)

## **Ingredients**

Water, shellac, larch bitumen, castor oil, linseed oil, colophony resin ester, polysaccharide, sodium poly-phosphate, turkey red oil, aliphatic hydrocarbon, borax, citral, lavender oil, thyme oil.

## **Preparing the Surface**

1. Prepare the surface in accordance with standard practice to AS/NZS 2311:2000
2. Apply to surfaces that have been pre-coated with the appropriate number of coats of The Natural Paint Company Wall Paint Primer Wall Paint – see relevant Data Sheets.
3. Ensure the surface is smooth, dry and clean.

**Note:** Tinted products are non-refundable.

## **Applying the Product**

1. Do not use below 5°C.
2. Ventilate well when working with the product and while it is drying.
3. Make trials first to find the colour and application method to achieve your desired finished look.
4. Make up the glaze solution to the desired colour (see instructions below).
5. The mixture can be applied by brush, roller, sponge or rag.
6. Subsequent coats can be different colours or strengths of colour.

## **Tinting and Mixing Instructions**

**Powder Pigment range:** The range of colours in The Natural Paint Company Lazure Glaze paint system can be enlarged dramatically by using our Powder Pigments. In order for the powder to be smoother and to enable it to be fully dissolved by the glaze, mix 50g pigment into 70-100mls water and leave to stand for at least 12 hours (stir periodically). Stir the Lazure Glaze into the pigment paste - a suggested recipe is: 200-300g of Lazure Glaze into 10g of pigment mixture and gradually thin with 600-700g of water. It is essential to combine slowly, working in well and to get it evenly combined.

For a more durable finish the quantity of Lazure Glaze can be increased. A final coat of 1-part Lazure Glaze: 1-2 parts water can be applied over the finished paint effect.



Always test for adhesion and compatibility on your substrate, particularly on already painted or questionable surfaces.

## Additional Information

A paint effect product for people who love to experiment and be creative with paint.

The product comes in two parts – the concentrated translucent glaze base (5L containers) and the colour pigment in the form of powder pigment.

The base wall colour is important to the final look. White or subtle colours are often used, but mid-range colours work well too as long as they are not too dominant for the glaze colours you are making. Always experiment first.

It's best to make up a sample board before you begin to see if you are happy with the finish. Keep a careful note of the recipes you used - and if you are happy with the test results proceed with painting your larger area.

Using more than one colour gives an interesting depth to the finished look. You can effectively build up many layers of colour.

Because everyone is wanting a different look, there is no 'set way' to use the glaze - you can use Lazure Glaze to colour wash, drag walls, rag (on or off), stippling etc

Examples:

**Dragging** - use a brush coated with glaze to run vertically down the base wall colour. You can alternate with two or more different colours.

**Ragging** – apply a small amount of product to a scrunched up dry rag and apply directly to the wall. This is ragging on. You can then use a second (or more) colour to add another layer of colour.

Lazure Glaze has a wonderful smell while it's being applied that comes from the thyme oil and lavender oil.

**DIY - If customer is applying themselves:** We'll be happy to talk you through the painting process when you're ready to paint.

**Non-DIY if the customer is using a tradesman:** We'll be happy to speak with your tradesman about the recommended techniques to achieve a high-quality finish.



QUESTIONS	Answer
Are they completely natural?	Yes, and they are nontoxic with a fabulous smell while wet.
Do you have a colour range I can see?	You can visit our Powder Pigments online to see instructions on how to see our range.
Can I paint Lazure over my existing wall colour?	Always test for compatibility first.

## **Drying**

- Allow a minimum of 3 hours between coats. Apply no more than 3 coats per day.
- 3 coats or less will be fully dry within 24 hours.

## **Cleaning**

- Clean implements immediately after use with water. Wash in sinks that flow to sewers, not storm water drains.

## **Maintenance**

- Clean only after fully hardened allow 14-21 days. Use a damp cloth with a gentle non-abrasive cleaner for surfaces coated with The Natural Paint Company Lazure Glaze.

## **Safety Precautions**

Natural ingredients can still be harmful to users and the environment if misused, or if accidents occur, so please carefully observe the following:

- Keep out of reach of children.

## **Storage**

- Keep tightly sealed in a cool, dry, frost free place.
- Use opened containers as quickly as possible.

## **Disposal**

- Do not dispose of in drains and wastepipes.
- Let waste dry out and recycle empty containers where possible. Dispose of according to council regulations.

## **Disclaimer**

The above information is given as a general guide only. Site conditions will vary, and it is always advisable to apply a test sample. Failure to follow the above instructions will void all warranties attached to the product. This supersedes any previous data sheets.

