

## Gib Primer/Sealer

### Description

A natural, environmentally responsible primer and sealer for use with The Natural Paint Company's Wall Paint. Pleasant smelling, VOC free\* and free of all other harmful chemicals. Use Natural Paint Co Gib Primer/Sealer on new or existing interior surfaces such as Gib board, plaster, plasterboard and MDF. Not Suitable for Aqualine Gib or other timber. Available in a spray or roller version. \*as defined by GREENGUARD of less than 5g of VOC/L

### Uses

As an interior primer/sealer for:

- New Gib board (excluding aqualine)
- New plaster and plasterboard
- Mud brick
- New, cured concrete – after a minimum curing time of 6 weeks
- Not recommended for timbers, metal or particle board - use The Natural Paint Company Undercoat/Pigmented Sealer or Specialty Undercoat – refer to Data Sheet.

### Coverage

- 12-14m<sup>2</sup> per litre depending on the absorbency of the substrate.

### Container Sizes

- 1 Litre, 2 Litre, 4 Litre, 10 Litre.

### Ingredients

Castor or safflower oil, lemon peel oil, borax, calcium carbonate, kaolin, titanium dioxide, water, cellulose, surfactant, tree resins, tetrasodium salt, iron oxides, earth pigments, non-hazardous biocides at less than 0.005%

### Preparing the Surface

Surface	Preparation/Primer	Top Coats
New Gib board, MDF	Apply 1 coat Gib Primer/Sealer.	Finish with 2 coats Wall & Ceiling Paint *



Surface	Preparation/Primer	Top Coats
New plaster, new concrete,	Apply 1 coat Wall Paint Primer after a minimum of 6 weeks curing.	Finish with 2 coats Wall & Ceiling Paint. *

\*Some colours and substrates may require extra topcoats. For a smoother finish sand lightly between coats using 180-240 grit paper.

Refer to Wall Paint Data Sheet for preparation information for the following surfaces: old, unpainted Gib board; previously coated Natural Wall Paint; acrylic paint; wallpaper (excluding vinyl wallpaper); new lining paper; old enamel and oil-based paints.

1. Prepare the surface in accordance with standard practice to AS/NZS 2311:2000.
2. Ensure the surface is smooth, dry and clean.
3. Use Natural Paint Co Thinner to remove any grease or hard to remove dirt and allow to dry.
4. Remove stains or seal off with a weak solution of shellac: 200-250 grams shellac per 1 litre methylated spirit.
5. Brush loose particles.
6. **Always test for adhesion and compatibility on your substrate.**

Note: Tinted products are non-refundable.

## **Applying the Product**

1. Do not use below 5°C.
2. Stir thoroughly before use. Leave to warm up if product has become cold.
3. Brush, roll or spray in an even coat.
4. Working in an area of no more than two to three roller widths at once, roll out Gib Primer/Sealer spreading it evenly. Then roll slowly with an even speed and light pressure over the same area working from top to bottom in one movement keeping as little overlap as possible. The Natural Paint Company Gib Primer/Sealer is very quick drying and rolling over product that has already dried or applying uneven pressure will result in roller marks.
5. Spraying details: Airless Spraying 412, 414 or 515 tip. Check spray equipment instructions and adjust from low pressure setting as required. **Only thin spray version up to 10%. Do not thin roller version of product.**

## **Drying**

- Touch dry in 30-60 minutes.
- Can be repainted after approximately 2-4 hours.



## **Cleaning**

- Clean implements immediately after use with warm soapy water. Wash equipment in sinks that flow to sewers not storm water drains.

## **Safety precautions**

Natural ingredients can still be harmful to users and the environment if misused, or if accidents occur, so please carefully observe the following:

- Keep out of reach of children.

## **Storage**

- Keep tightly sealed in a cool, dry, frost-free place.

## **Disposal**

- Do not dispose of in drains and wastepipes.
- Let waste dry out and recycle empty containers where possible. Dispose of according to council regulations.

## **Disclaimer**

The above information is given as a general guide only. Site conditions will vary, and it is always advisable to apply a test sample. Failure to follow the above instructions will void any implied warranties attached to the product. This supersedes any previous data sheets.

