

Pure Interior Oil

Description

A durable interior oil, based on natural ingredients and renewable resources. The Natural Paint Company Pure Interior Oil comes in range of trans oxide colours, is solvent free, VOC free and is approved for use on toys according to European regulations.

Pure interior oil is an excellent alternative to other natural oils or chemical polyurethane for walls and ceilings and will not cause light woods to go golden like a varnish, helping to retain the natural colour of woods. Available in a Matt, Semi-Gloss or Gloss finish. Clean up with water.

Uses

As an oil finish for interior surfaces, including:

- Timber surfaces, such as walls, ceilings, windows, doors, sills, mouldings, toys and furniture. Can be used on MDF, chip board, plywood.

Coverage

- 8-14m² per litre depending on the absorbency of the substrate.

Container Sizes

- 500mls, 1 Litre, 2 Litre, 4 Litre, 10 Litre

Ingredients

Dehydrated castor oil, colophony resin ester, anti-oxidants, clay, zinc oxide, Proprietary complex driers (non-hazardous).

Preparing the Surface

1. Prepare the surface in accordance with standard practice.
2. For reapplication of Pure Interior Oil see 'Maintenance'.
3. Other surface coatings may need to be removed completely.
4. The surface must be well sanded: General recommendation is 180-240 grit.
5. Ensure the surface is clean, free from grease and dry with a maximum moisture content of 12%.
6. Wipe timbers containing high amounts of resins or terpenes with The Natural Paint Company Thinner, using a lint free cloth - especially on rimu, matai, oak, some tropical timbers, etc. Allow to dry.
7. If glue is used, ensure it is fully hardened before applying product.



8. Always test for suitability on your substrate with an adhesion test.

Applying the Product

1. Do not apply below 12°C.
2. Stir thoroughly before use.
3. Ventilate well when working with the product and while it is drying.
4. Apply 2 - 3 coats of Pure Interior Oil by brush, roller or spray-gun.
5. Spraying details: Airless Spraying fine finish 210 or 310 tip. For broad walls use 412, 414 or 515

Tip: Check spray equipment instructions and adjust from low pressure setting as required. Do not thin product.

Drying

- Touch dry after 1-2 hours at 20°C at 50-55% humidity.
- Can be sanded and/or recoated after 3 hours at 20°C at 50-55% relative humidity. Fully hardened after 7-14 days.

Note: The drying time of oil-based products is prolonged by:

High humidity and/or low temperatures during application and drying time; absorption of natural terpenes, oils, waxes or resins from the substrate, poor ventilation and thick coats.

Cleaning

- Clean implements immediately after use with water. If left, implements will need to be cleaned up with thinners.

Maintenance

- Clean only after fully hardened. Use warm soapy water to clean surfaces coated with Pure Interior Oil. We recommend a non-caustic, gentle household cleaner.
- To recoat, degrease surface. A light sand may be needed to ensure adhesion. Apply 1 - 2 coats according to application instructions.

Safety Precautions

Natural ingredients can still be harmful to users and the environment if misused, or if accidents occur, so please carefully observe the following:

- Keep out of reach of children.
- Use with adequate ventilation; do not breathe fumes or vapour.
- Avoid skin contact.
- Keep work materials soaked in Pure Interior Oil, such as rags, sponges, sanding dust and contaminated clothing in an airtight container, or rinse in water and spread out to dry on a non-combustible surface.



Storage

- Seal well and store in a cool and dry place.
- Remove any skin that has formed in open containers and sieve if necessary before use.

Disposal

- Do not dispose of in drains and wastepipes.
- Let waste dry out and recycle empty containers where possible. Dispose of according to council regulations.

Disclaimer

The above information is given as a general guide only. Site conditions will vary, and it is always advisable to apply a test sample. Failure to follow the above instructions will void all warranties attached to the product. This supersedes any previous data sheets.

